



3/8 WIRE ROPE 8 GPM 2850 PSI STALL			
LAYER	CAPACITY (FT)	LIFT (LBS)	SPEED (FPM)
1	40	6026	54
2	85	5511	59
3	132	5077	64
4*	184	4707	69
*FREEBOARD RATIO = 0.83			

7/16 WIRE ROPE 8 GPM 2850 PSI STALL			
LAYER	CAPACITY (FT)	LIFT (LBS)	SPEED (FPM)
1	34	5984	54
2	72	5406	60
3	114	4930	66
4*	159	4531	72
*FREEBOARD RATIO = 0.14			

1/2 WIRE ROPE 8 GPM 2850 PSI STALL			
LAYER	CAPACITY (FT)	LIFT (LBS)	SPEED (FPM)
1	30	5939	55
2	64	5297	61
3*	102	4780	68
*FREEBOARD RATIO = 0.62			

NOTES:

1. DRUM ACCEPTS $\phi 3/8$ TO $\phi 1/2$ WIRE ROPE
2. WINCH MOTOR: PARKER, 15.9 CID, 6B SPLINE
3. WINCH SHIPPED WITH 2 QTS, EP80W90 LUBRICANT; VENT HOLE IS PLUGGED AND VENT SHIPPED SEPARATELY
4. PAINTED BLACK WITH ALKYD ENAMEL
5. 5:1 GEAR RATIO